



T-Lok Barrier



The T-Lok Barrier is a freestanding, temporary redirective longitudinal barrier successfully crash tested to MASH TL-3.

Featuring a new and improved design, this precast concrete F-type barrier has an Austroads Safety Barrier Assessment Panel (ASBAP) approval to 100km/h.

Anti sight / debris screens can be fitted to the barriers providing additional protection for workers from items falling off passing trucks, as well as reducing the risk to motorists from "gawking" drivers becoming distracted or slowing unexpectedly when passing roadworks.

- ✓ Freestanding barrier
- ✓ Low deflection
- ✓ Safe redirection
- ✓ Fast deployment and retrieval
- ✓ No anchoring required
- ✓ Maintenance free
- ✓ Multiple end treatments can be used
- ✓ Sight / debris screen options bolt on
- ✓ Available in either 3.6m or 5.4m lengths

SPECIFICATIONS

Product code	3.6M F1303000 OR 5.4M F1303001
Effective Length	3.65m / 5.48m
Height	810mm
Width	610mm
Weight	2600kg/3900kg
Weight Per Metre	722kg
Successfully Tested To	MASH TL-3
ASBAP Approval To	100km/h
MASH TL-3 Deflection	1.27m
Amount Transportable Per Semi Truck	9 or 6

Approved by:

